CRASH TESTED BOLLARDS

Crash Tested Safety Bollard – 15 mph Asphalt

A 15 mph crash-tested safety bollard designed for asphalt surfaces, certified to ASTM F3016.

Product code **52720544** | Cover **Plastic or stainless**



15 mph	2,268 kg	ASTM F3016	1016 mm
tested impact speed (24 km/h)	5,000 lb pickup truck	crash test standard	height above ground

Overview

A crash-tested safety bollard, tested at an independent third-party laboratory with a 5,000 lb (2,268 kg) pickup truck travelling at 15 mph (24 km/h). It protects shop fronts, entrances, walkways and people from vehicle impact.

It is more than a strong post: it is a complete, kitted safety system with a choice of covers to suit the look of your site.

Key features

- **Crash tested at 15 mph** with a 2,268 kg vehicle
- **ASTM F3016** certified
- **Designed for asphalt** surfaces
- **Supplied as a kit:** core, cover, rebar cage and fixings
- **Choice of covers:** plastic, with or without reflective strips, or stainless steel
- **Third-party crash tested** at an independent laboratory

Store Fittings Direct is a trading name of CHF Solutions Ltd, registered in England & Wales 12316756. Specification may change without notice. © 2026 Store Fittings Direct. Not to be copied or reproduced without permission.

Scan to view online

Specification

Product code	52720544
Crash rating	
Standard	ASTM F3016
Test vehicle	5,000 lb (2,268 kg) pickup truck
Impact speed	15 mph (24 km/h)
Testing	Independent third-party laboratory
Dimensions and covers	
Height above ground	1016 mm (40")
Steel core	4" (102 mm) diameter
Plastic cover	4" (133 mm diameter), with or without reflective strips
Stainless steel cover	6" (168 mm diameter)
Surface	Designed for asphalt surfaces
Supply	
Kit includes	Core, cover, rebar cage and fixings (concrete not included)

store fittings direct

Why an asphalt version?

Most crash-tested bollards are designed for concrete. This version is designed and tested for asphalt car parks and roads, so you get the same 15 mph protection without breaking out the surface for a concrete slab.

Choosing a cover

4" plastic cover (133 mm diameter) is the cost-effective choice, available plain or with reflective strips for extra visibility in car parks.

6" stainless steel cover (168 mm diameter) gives a premium finish for shop fronts and entrances.



Crash tested bollards with yellow covers on an asphalt car park.

Talk to someone who sells this every day

Tell us what you need to protect and the approach speed of vehicles, and we will help you choose the right rating.

Call 0116 318 4182

Store Fittings Direct is a trading name of CHF Solutions Ltd, registered in England & Wales 12316756. Specification may change without notice. © 2026 Store Fittings Direct. Not to be copied or reproduced without permission.

Scan to view online