
FULL HEIGHT TURNSTILES

Dalby Full Height Turnstile Pedestrian Gate

A heavy-duty single full height turnstile for secure perimeters, construction sites and depots, rated for continuous operation under heavy foot traffic.

Product code **92870397** | Lanes **1** | Use **Internal or external**



2175 mm
full height, floor to canopy frame

120°
three-arm rotor as standard, 90° optional

100%
duty cycle rated for continuous use

IP56
rated control panel enclosure

Overview

A full height turnstile built from steel for perimeter security, whether it controls a main site entrance, forms part of a perimeter fence system or is added into an existing fence line. It is compact enough for internal use where ceiling height is limited.

The mechanism is smooth and quiet, and the turnstile is 100% duty cycle rated for heavy, continuous foot traffic. Link it to card readers, keypads or biometric readers to control who gets in and to record staff movement for time and attendance or health and safety.

Key features

- **Steel frame and rotor** for rugged, long-term use outdoors
- **Three finishes:** zinc primed and powder coated, galvanised, or galvanised and powder coated
- **Fail locked or fail unlocked** head mechanism on power failure, your choice
- **Counting outputs and fire alarm inputs** as standard
- **Manual emergency override** included
- **Optional canopy,** lights, trombone arms and matching pedestrian gate

Store Fittings Direct is a trading name of CHF Solutions Ltd, registered in England & Wales 12316756. Specification may change without notice. © 2026 Store Fittings Direct. Not to be copied or reproduced without permission.

Scan to view online

Specification

Product code	92870397
Construction	
Frame	Steel
Rotor	Steel
Rotor configuration	Straight arm 120° (three-arm) as standard; 90° straight arm or trombone arms as options
Passage	Single lane
Finish	
Options	Zinc primed and smooth powder coated; galvanised; galvanised and smooth powder coated
Colour	Black (RAL 9005) as standard. Also RAL 3003, 3020, 1023, 2004, 6005, 6032, 6018, 5003, 5002, 5017, 9006, 7001 and 9010 on extended lead time
Size	
Overall size W × D × H (mm)	1450 × 1200 × 2175
Electrical	
Supply	230 V, single phase, 50 Hz
Load	3 A
Control panel	Electrical enclosure rated IP56
Power failure	Fail locked or fail unlocked head mechanism (specify at order)
Interfaces	Counting outputs and fire alarm inputs as standard
Emergency override	Manual control included as standard
Access control	
Compatible with	Card readers, digital keypads, push buttons, biometric readers and intercom systems
Options	
Accessories	Overhead canopy, lights, matching pedestrian gate
Supply	Flat packed or fully assembled

Delivered by flatbed vehicle and offloaded by others. A Hi-ab offloading service is available on request.

Store Fittings Direct is a trading name of CHF Solutions Ltd, registered in England & Wales 12316756. Specification may change without notice. © 2026 Store Fittings Direct. Not to be copied or reproduced without permission.

Scan to view online

Controlling access

Credential in. Pair the turnstile with a card reader, keypad, push button, biometric reader or intercom so only authorised people can pass.

Count movements. Counting outputs come as standard, so you can track how many people have entered or left a site.

Safe in an emergency. Fire alarm inputs are standard, and the head can be specified to lock or free on power failure to suit your site.

Choosing the right set-up

Choose the single turnstile for one lane, or the double turnstile where two lanes of traffic need to pass at once.

For coastal or very exposed sites, the galvanised and powder coated finish gives the best protection. Standard colours other than black add to the lead time.

Add the matching pedestrian gate alongside for deliveries, wheelchairs and equipment that will not pass through the rotor.



Galvanised finish with overhead canopy, shown with a matching pedestrian gate.

Talk to someone who sells this every day

Tell us about your site, how many people pass through and what access control you use, and we will help you choose the finish and options.

Call 0116 318 4182

Store Fittings Direct is a trading name of CHF Solutions Ltd, registered in England & Wales 12316756. Specification may change without notice. © 2026 Store Fittings Direct. Not to be copied or reproduced without permission.

Scan to view online