DOOR GUARDS

Door Guard Protection Stopper

A steel door guard with a central rubber stopper, 1100 × 800 mm, that stops swinging doors damaging walls.

Product code **90686597** | Size **1100 × 800 mm**



1100 mm	800 mm	Rubber	3 finishes
high	wide	stopper	galv, colour, stainless

Overview

A door guard that protects walls from damage by swinging doors. A central rubber stopper absorbs the shock and stops the door hitting the steel frame.

It suits commercial and industrial sites, inside or out, and can be used singly or in pairs. Choose plates for bolting down or extended legs for concreting in. Made to order.

Key features

- **Rubber stopper** absorbs the impact
- **Steel frame** 2 mm wall
- **Three finishes** galvanised, coloured or stainless
- **Bolt down or concrete in** options
- **Made to order** single or in pairs

Where it is used

Fire exits, external doors, service doors and wide doorways in shops, warehouses and public buildings.

Root fixed or surface fixed?

Root fixed guards are concreted into the ground. **Surface fixed** guards bolt onto an existing concrete surface.

Store Fittings Direct is a trading name of CHF Solutions Ltd, registered in England & Wales 12316756. Specification may change without notice. © 2026 Store Fittings Direct. Not to be copied or reproduced without permission.

Scan to view online

Specification

Product code	90686597
Dimensions	
Size (H × W)	1100 × 800 mm
Wall thickness	2 mm
Tapping rail	50 × 5 mm
Base plates	Round, 120 × 5 mm
Root fixed legs	300 mm below ground
Finish	
Finishes	Galvanised, galvanised and powder coated, or stainless steel
Options	
Fixing	Root fixed or surface fixed



Powder coated black.

Talk to someone who sells this every day

Tell us about your site and what you need to protect, and we will help you choose the right barrier.

Call 0116 318 4182