DOOR GUARDS

# Door Guard Safety Barrier with Infill

A hoop door guard with a solid or perforated infill panel, stopping outward-opening doors from swinging back into walls or glazing.



Product code **68960846**

Infill **Solid or perforated**

| 1100 mm | 800 mm | 2 infills | 3 finishes |
|---|---|---|---|
| height | width | solid or perforated | galvanised, powder coated, stainless |

## Overview

A door guard is a hoop barrier fitted outside an outward-opening door, such as a fire exit or service door. It stops the door swinging back too far and hitting walls, and a built-in rubber stopper cushions the door so it does not hit the steel frame.

This version has an infill panel filling the centre of the hoop. The panel protects the wall or glazing behind the guard and gives a neater, more finished look.

## Key features

- **Infill panel** solid or perforated
- **Rubber stopper** cushions the door
- **Internal or external** use, on its own or in pairs
- **Root or surface fixed** options
- **Seven powder coat colours** to choose from
- **Made to order**

**Store Fittings Direct** is a trading name of CHF Solutions Ltd, registered in England & Wales 12316756. Specification may change without notice. © 2026 Store Fittings Direct. Not to be copied or reproduced without permission.



Scan to view online

## Specification

| Product code | 68960846 |
|---|---|
| **Dimensions** | |
| **Height** | 1100 mm |
| **Width** | 800 mm |
| **Frame** | 2 mm wall thickness |
| **Tapping rail** | 50 mm × 5 mm |
| **Infill and stopper** | |
| **Infill** | Solid / plain or perforated panel |
| **Stopper** | Central rubber stopper to cushion the door |
| **Fixing options** | |
| **Root fixed** | Legs concreted in 300 mm below ground |
| **Surface fixed** | Round base plates, 120 mm × 5 mm |
| **Finish** | |
| **Options** | Galvanised; galvanised and powder coated; or stainless steel |
| **Powder coat colours** | Traffic Red RAL 3020, Rape Yellow RAL 1021, Traffic Blue RAL 5017, Moss Green RAL 6005, Silver Grey RAL 7001, Jet Black RAL 9005, Pure White RAL 9010 |
| **Application** | |
| **Locations** | Warehouses, factories, retail units, schools and commercial buildings, inside or out |
| **Supply** | Made to order |

**Store Fittings Direct** is a trading name of CHF Solutions Ltd, registered in England & Wales 12316756. Specification may change without notice. © 2026 Store Fittings Direct. Not to be copied or reproduced without permission.



Scan to view online

## Solid or perforated infill?

A **solid** panel gives a clean, simple look and a full screen.

A **perforated** panel has a more decorative look and lets you see through it.

**Root fixed** legs are concreted 300 mm into the ground; **surface fixed** guards have round base plates for an existing concrete slab.

## Which finish?

**Galvanised** is the most cost-effective option and protects against rust.

**Galvanised and powder coated** adds a colour finish on top of the galvanising.

**Stainless steel** is the premium choice for front-of-house entrances where appearance matters.




Door guard with solid infill outside a service door.

### Talk to someone who sells this every day

Tell us about your doors and site, and we will help you choose the infill, finish and fixing.

Call 0116 318 4182

**Store Fittings Direct** is a trading name of CHF Solutions Ltd, registered in England & Wales 12316756. Specification may change without notice. © 2026 Store Fittings Direct. Not to be copied or reproduced without permission.



Scan to view online