LOADING BAY

HGV Wheel Guide

A galvanised steel wheel guide, 1500 or 2000 mm long and 320 mm high, that guides lorries safely back into loading bays.

Product code **72803306** | Height **320 mm**



139 / 168	1500 / 2000	320 mm	Bolt
diameters, mm	lengths, mm	high	down

Overview

A solid steel kerb that guides lorries and delivery vehicles safely as they reverse into a loading bay. It can also protect racking, equipment and machines from forklifts and vehicles.

It is made from galvanised mild steel tube with a 5 mm wall, and can be powder coated yellow for extra visibility. Sold singly, bolt down only.

Key features

- **Galvanised steel tube** 5 mm wall
- **Two diameters** 139 or 168 mm
- **Two lengths** 1500 or 2000 mm
- **Yellow coating** option
- **Square base plates** 250 × 10 mm

Where it is used

Loading bays and docks, service yards, racking ends and around machinery.

Straight or cranked?

Straight guides line the sides of a bay. **Cranked** guides flare out at the entrance to steer the wheels in.

Store Fittings Direct is a trading name of CHF Solutions Ltd, registered in England & Wales 12316756. Specification may change without notice. © 2026 Store Fittings Direct. Not to be copied or reproduced without permission.

Scan to view online

Specification

Product code	72803306
	Dimensions
Tube	139 or 168 mm diameter, 5 mm wall
Lengths	1500 or 2000 mm
Height	320 mm
Base plates	250 mm square × 10 mm
	Finish
Finishes	Galvanised, or galvanised and powder coated yellow
	Supply
Sold	Singly
Fixing	Bolt down only



Galvanised finish.

Talk to someone who sells this every day

Tell us about your site and what you need to protect, and we will help you choose the right barrier.

Call 0116 318 4182