TELESCOPIC BOLLARDS

Padlockable Telescopic Bollard – 500 mm

A telescopic bollard, 500 mm above ground when raised, that lowers fully into the ground when vehicles need access.

Product code **90492801** | Height **500 mm raised**



500 mm	60–90	Flush	Padlock
raised height	diameters, mm	lid when lowered	secured

Overview

A telescopic bollard that gives a robust way to protect premises and vehicles. It is raised and lowered vertically, standing 500 mm above ground when up and sitting fully below ground when down, covered by its integral lid.

When raised it is secured with a padlock (not supplied). It is ideal for vehicle forecourts, commercial premises, car parks and domestic driveways.

Key features

- **Telescopic** lowers fully below ground
- **Integral lid** leaves the surface flush when down
- **Padlockable** padlock not supplied
- **3 sizes** from 60 to 90 mm
- **Galvanised steel** with colour coating options

Store Fittings Direct is a trading name of CHF Solutions Ltd, registered in England & Wales 12316756. Specification may change without notice. © 2026 Store Fittings Direct. Not to be copied or reproduced without permission.

Scan to view online

Specification

Product code	90492801
Dimensions	
Height above ground (raised)	500 mm
Sizes	60, 76, 90 mm diameter
Wall thickness	3 mm galvanised, 2 mm stainless steel
Socket depth	760 mm below ground
Finish	
Material	Galvanised steel
Options	Galvanised; galvanised and colour coated; or stainless steel (76 and 90 mm)
Operation	
Type	Telescopic, raised and lowered vertically
Lock	Padlockable in the raised position (padlock not supplied)
Lid	Integral lid covers the socket when lowered

Store Fittings Direct is a trading name of CHF Solutions Ltd, registered in England & Wales 12316756. Specification may change without notice. © 2026 Store Fittings Direct. Not to be copied or reproduced without permission.

Scan to view online

How it works

To raise. Lift the post up out of its socket, rotate it 45° and fit a padlock between the post and the lid.

To lower. Remove the padlock, rotate the post back and lower it fully into the ground. Close the integral lid so the surface is left flush.

Where it is used

Vehicle forecourts, commercial premises, car parks, private roads and domestic driveways.

Matches our fixed and removable bollards for mixed runs.



Telescopic bollard shown raised.

Talk to someone who sells this every day

Tell us about your site and what you need to protect, and we will help you choose the right bollards.

Call 0116 318 4182