TELESCOPIC BOLLARDS

Square Locking Telescopic Bollard – 745 mm

A square telescopic bollard, 745 mm above ground when raised, that lowers fully into the ground when vehicles need access.

Product code **87806672** | Height **745 mm raised**



745 mm	60–90	Flush	Push-button
raised height	square sizes, mm	lid when lowered	7-pin lock

Overview

A telescopic bollard that gives a robust way to protect premises and vehicles. It is raised and lowered vertically, standing 745 mm above ground when up and sitting fully below ground when down, covered by its integral lid.

When raised it is secured with an integral high-security 7-pin push-button lock. It is ideal for vehicle forecourts, commercial premises, car parks and domestic driveways.

Key features

- **Telescopic** lowers fully below ground
- **Integral lid** leaves the surface flush when down
- **High-security lock** 7-pin push button, key supplied
- **3 sizes** from 60 × 60 mm to 90 × 90 mm
- **Galvanised steel** with colour coating options

Store Fittings Direct is a trading name of CHF Solutions Ltd, registered in England & Wales 12316756. Specification may change without notice. © 2026 Store Fittings Direct. Not to be copied or reproduced without permission.

Scan to view online

Specification

Product code	87806672
Dimensions	
Height above ground (raised)	745 mm
Sizes	60 × 60 mm, 70 × 70 mm, 90 × 90 mm
Wall thickness	3 mm
Socket depth	1070 mm below ground
Finish	
Material	Square mild steel tube, galvanised
Options	Galvanised; galvanised and black; or galvanised and yellow
Operation	
Type	Telescopic, raised and lowered vertically
Lock	Integral high-security 7-pin push-button lock, key supplied
Lid	Integral lid covers the socket when lowered
Extras	Red and white chevron tape available

Store Fittings Direct is a trading name of CHF Solutions Ltd, registered in England & Wales 12316756. Specification may change without notice. © 2026 Store Fittings Direct. Not to be copied or reproduced without permission.

Scan to view online

How it works

To raise. Unlock with the key, lift the post up out of its socket, rotate it 45° and press the push-button lock to secure it.

To lower. Unlock with the key, rotate the post back and lower it into the ground. Close the integral lid so the surface is left flush.

Where it is used

Vehicle forecourts, commercial premises, car parks, private roads and domestic driveways.

Matches our fixed and removable bollards for mixed runs.



Galvanised and coated black version.

Talk to someone who sells this every day

Tell us about your site and what you need to protect, and we will help you choose the right bollards.

Call 0116 318 4182