REMOVABLE BOLLARDS

Stainless Steel Removable Locking Bollard – 900 mm

A removable stainless steel ground post, 900 mm above ground, with an integral high-security lock and a socket lid that covers the hole when the post is out.

Product code **64400501**

Height **900 mm above ground**



900 mm	76–168	7-pin	Sold Secure
above ground	diameters, mm	push-button security lock	tested and approved

Overview

A highly effective and robust way to protect premises and vehicles. When the post is removed, an integral lid covers the socket so the ground is left flush and safe.

To lock it, rotate the post 45° and press the high-security 7-pin push-button lock. Unlock it with the key supplied, rotate it back and lift it out. It is ideal for vehicle forecourts, commercial premises, car parks and driveways.

Key features

- **Integral lock** high-security 7-pin push button
- **Socket lid** covers the hole when removed
- **Sold Secure** tested and approved
- **Secured by Design** status
- **6 diameters** from 76 mm to 168 mm
- **Reflective bands** available as an extra

Store Fittings Direct is a trading name of CHF Solutions Ltd, registered in England & Wales 12316756. Specification may change without notice. © 2026 Store Fittings Direct. Not to be copied or reproduced without permission.

Scan to view online

Specification

Product code	64400501
Dimensions	
Height above ground	900 mm
Diameters	76, 90, 101, 114, 139, 168 mm
Wall thickness	2 mm
Socket depth	265 mm (76 and 90 mm) or 280 mm (101–168 mm) below ground
Finish	
Material	304-grade brushed stainless steel
Options	Brushed stainless steel
Security	
Lock	Integral high-security 7-pin push-button lock, key supplied
Approvals	Sold Secure tested and approved; Secured by Design status
Extras	Reflective bands available

Store Fittings Direct is a trading name of CHF Solutions Ltd, registered in England & Wales 12316756. Specification may change without notice. © 2026 Store Fittings Direct. Not to be copied or reproduced without permission.

Scan to view online

How it works

To lock. Drop the post into its socket, rotate it 45° and press the push-button lock.

To remove. Unlock it with the key, rotate it back and lift it out. Close the integral lid over the socket.

Where it is used

Vehicle forecourts, commercial premises, car parks, private roads and domestic driveways.



The socket with its integral lid and push-button lock.

Talk to someone who sells this every day

Tell us about your site and what you need to protect, and we will help you choose the right bollards.

Call 0116 318 4182